





TO-126 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	2.500	2.900	0.098	0.114
A1	1.100	1.500	0.043	0.059
b	0.660	0.860	0.026	0.034
b1	1.170	1.370	0.046	0.054
c	0.450	0.600	0.018	0.024
D	7.400	7.800	0.291	0.307
E	10.600	11.000	0.417	0.433
e	2.290 TYP		0.090 TYP	
e1	4.480	4.680	0.176	0.184
h	0.000	0.300	0.000	0.012
L	15.300	15.700	0.602	0.618
L1	2.100	2.300	0.083	0.091
P	3.900	4.100	0.154	0.161
ϕ	3.000	3.200	0.118	0.126



- 技术要求
1. 塑封体尺寸10.80×7.60;
 2. 未注公差为: ±0.05;
 3. 所有单位为: mm。

中心距: 2.29
 脚宽: 0.76
 焊盘宽: 1.20
 脚厚: 0.50
 焊盘厚: 1.00

媒体编号

镀涂

旧底图总号

底图总号

更改标记	数量	更改单号	签名	日期
设计				
审核				
工艺				
标准化				
批准				

T0-126 焊 盘

等级标记 | 版 号 | 比 例

10:1

第 1 张 共 1 张

江苏长电科技股份有限公司


日期 | 签名

格式 (1)

制 图:

描 图:

幅 面: A4





Inner Box: 240 mm × 165mm × 95mm



Label on the Inner Box

Stamp "EMPTY"
on the empty box



Outer Box: 525 mm × 360mm × 262mm

Seal the box
with the tape

QA Label



Label on the Outer Box