





TO-252-3L PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
c	0.430	0.580	0.017	0.023
c1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP		0.091 TYP	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
V	3.80 REF		0.150 REF	



技术要求

1. 塑封体尺寸 6.50×5.50 ;
2. 未注公差为: ± 0.05 ;
3. 所有单位为: mm。

媒体编号

镀 涂

旧底图总号

T0-252-3L
焊 盘

底图总号

更改标记	数量	更改单号	签 名	日 期
设 计				
审 核				
工 艺				
标 准 化				
批 准				

等级标记		版 号	比 例
		A	10:1
第 1 张		共 1 张	


江苏长电科技股份有限公司

格式 (1)

制 图:


描 图:

幅 面: A4






Inner Box: 340 mm×336mm×29mm



Label on the Reel



Label on the Inner Box



Stamp "EMPTY"
on the empty box

Outer Box: 353 mm× 346mm× 365mm



Seal the box
with the tape

QA Label



Label on the Outer Box

Common Packing: (5 inner boxes/carton)



Common Packing: (10 inner boxes/carton)

