

TO-92 Plastic-Encapsulate Transistors

3DD13002S TRANSISTOR (NPN)


FEATURES

Power switching applications

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	600	V
V_{CEO}	Collector-Emitter Voltage	400	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current -Continuous	1	A
P_C	Collector Power Dissipation	0.75	W
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	167	$^{\circ}\text{C}/\text{W}$
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature	-55~+150	$^{\circ}\text{C}$

TO-92



- 1. EMITTER
- 2. COLLECTOR
- 3. BASE

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = 0.1\text{mA}, I_E = 0$	600			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, I_B = 0$	400			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = 0.1\text{mA}, I_C = 0$	6			V
Collector cut-off current	I_{CBO}	$V_{CB} = 600\text{V}, I_E = 0$			100	μA
Collector cut-off current	I_{CEO}	$V_{CE} = 400\text{V}, I_B = 0$			100	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = 7\text{V}, I_C = 0$			100	μA
DC current gain	$h_{FE(1)}$	$V_{CE} = 10\text{V}, I_C = 200\text{mA}$	9		40	
	$h_{FE(2)}$	$V_{CE} = 10\text{V}, I_C = 250\mu\text{A}$	5			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 200\text{mA}, I_B = 40\text{mA}$			0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = 200\text{mA}, I_B = 40\text{mA}$			1.1	V
Transition frequency	f_T	$V_{CE} = 10\text{V}, I_C = 100\text{mA}, f = 1\text{MHz}$	5			MHz
Fall time	t_f	$I_C = 1\text{A}, I_{B1} = I_{B2} = 0.2\text{A}, V_{CC} = 100\text{V}$			0.5	μs
Storage time	t_s	$I_C = 1\text{A}, I_{B1} = I_{B2} = 0.2\text{A}, V_{CC} = 100\text{V}$			2.5	μs



CLASSIFICATION of $h_{FE(1)}$

Range	9-15	15-20	20-25	25-30	30-35	35-40
-------	------	-------	-------	-------	-------	-------

CLASSIFICATION of $V_{CE(sat)}$


Rank	A	B
Range	<0.25	0.25-0.45

TO-92 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.400	4.700	0.173	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Φ		1.600		0.063
h	0.000	0.380	0.000	0.015

TO-92 Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE


JCET reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JCET does not assume any liability arising out of the application or use of any product described herein.

TO-92 PACKAGE TAPEING DIMENSION



Dimiensions are in millimeter

A1	A	T	P	P0	P2	F1	F2	W
4.5±0.2	4.5±0.2	3.5±0.2	12.7±0.3	12.7±0.2	6.35±0.3	2.5±0.3	2.5±0.3	18.0+1.0/-0.5
W0	W1	W2	H	H0	D0	t1	t2	ΔP
6.0±0.5	9.0±0.5	1.0 MAX.	19.0±1.0	16.0±0.5	4.0±0.5	0.4±0.05	0.2±0.05	0 ± 1.0



Package	Box	Box Size(mm)	Carton	Carton Size(mm)
TO-92	2000 pcs	333×162×43	20,000 pcs	350×340×250